

In addition to the electric range, we also manufacture a range of diesel static machines. Choose from either a brushed stainless steel (316) cabinet or the popular powder coated stainless steel option.

Available in either single or three-phase power options, with a wide range of other specifications to suit all requirements.

Trusted by some of the UK's largest main dealer garages as well clients in other high volume wash environments such as vehicle auctions, dealerships, hauliers and many other fleet management surroundings.

Product Benefits

- Robust, secure and durable design to withstand the rigors of a high volume wash environment
- Easy to use front wash mode control panel
- Hinged top lid and lockable secure cabinet front door
- · Market leading high pressure CAT pump
- Cost effective purchase with capital purchase and rental options available
- · Full Electrajet chemical supply options
- Smart boiler control system to prevent overheating and unnecessary fuel wastage
- · Single & three-phase options to suit all install areas
- · Service & maintenance package

Purchase Options

- · Capital purchase
- Rental purchase with service and chemical plans included

Product Features

- Total Frost Protection
- · Feed Line Protection
- · Night Time Security Mode
- Auto Stop
- · Leak Detect
- · Smart Boiler Control System
- · Sleep Mode
- · Wake Mode
- · Low Water Warning
- · Chemical Line Feed

Optional Features

- · Auto Stop & Start
- · Compressed Air Blow Down
- · 150ltr Chemical Tank
- Waxing Pump

Cabinet Options

- · Brushed Stainless Steel (316)
- · Powder Coated Stainless Steel
- · Lockable Hinged door
- · Hinged Top Lid

| (4.5) | | | 7 MI2 | Company Callynder | | |
|--------------------|-------------------|-------------------|-------------------|-------------------|--------------------------------------|--------------------------------------|
| | ECO PDRS1 | PDRS2 | PDRS3 | PDRS4 | PDRS5 | PDRS6 |
| Voltage | Single-phase 230v | Single-phase 230v | Single-phase 230v | Single-phase 230v | Three-phase 415v | Three-phase 415v |
| Load | 13 A | 13 A | 17 A | 21 A | 3 x 8 A | 3 x 12 A |
| Water Flow | 12 l/min | 13 l/min | 13 l/min | 13 l/min | 15 or 21 I/min | 15 or 21 l/min |
| Output Pressure | 100bar / 1450psi | 100bar / 1450psi | 120bar / 1650psi | 150bar / 2000psi | 150bar / 2000psi 200bar / 2900psi | 150bar / 2000psi 200bar / 2900psi |
| Max Temperature | 0-70°C | 0-95°C | 0-95°C | 0-95°C | 0-95°C | 0-95°C |
| Motor | 3hp / 2.2kW | 3hp / 2.2kW | 4hp/3kW | 5.5hp / 4kW | 5.5hp / 4kW | 7hp / 5.5kW 10hp / 7.5kW |
| Boiler Capacity | 12 l/min | 15 l/min | 15 I/min | 15 I/min | 15 l/min | 15 or 21 I/min |
| Fuel Tank Capacity | 105 ltr | 105 ltr |